

ICON

2000



Product
Brochure



ICON2000 Release 2004: share your valve process information!

In the communication era, Biffi Italia has engineered new advanced solutions to easily communicate with on-field users and control rooms and to download all the process information and diagnostic data

ICON2000 v4: an important goal in the valve/actuator process diagnostics and advanced maintenance program



Features

More than half a century ago Biffi started its business in valve actuation.

Its world-wide leadership has been built through continuous innovation and the ability to face the new challenges that a fast changing environment comes up with.

It was in 1992 that Biffi started its intelligent actuator campaign.

Since then Biffi Intelligent actuators have been welcomed by all major companies around the world, in many different applications: platforms, deep tropical forest, Siberian chill and harsh desert environment.

With ICON2000, we made a further step forward towards ease of use and maintenance.

Release 2004 of ICON2000 introduces a new philosophy in the construction of electric actuators electronic cards: all major optional functions are integrated in the base card, which allows easy plug-in of future upgrades.

- ☐ Engineered as an improvement and optimization of the performances of the existing ICON2000 and totally interchangeable with Release 2000
- ☐ Actuator operation, setting and diagnostics are available via the integral user-friendly push-button panel
- ☐ IrDA(*) (Infra red Data Acquisition) communication available
- ☐ Bluetooth™, radiofrequency wireless connector based on a qualified Bluetooth™ class 1 module(**)
- ☐ Watertight and explosion-proof PDAs are available from Biffi Italia for actuator operation, download of diagnostic info, non-intrusive upgrading of firmware and for maintenance purposes through IrDA(*) or Bluetooth™
- ☐ Enhanced hardware and software performances to offer:
 - advanced maintenance data including reports on the last opening and closing position/torque curves with relative parameters and with direct comparisons with reference curves;
 - detailed and updated information on actuator internal parameters with precise and clear alarm reports, with both General and Recent (partial) log;
 - "Data logger" function for collecting different types of data for maintenance or diagnostic programs, available both in:
 - RECORDER mode for measurement and memorization of main actuator internal parameters with configurable SAMPLING TIME and START DATE and TIME
 - EVENT mode with memorization of OPEN or CLOSE commands, including indication of source, date and time with configurable START DATE and TIME

(*) IrDA not available in Japan and UK

(**) EP and US patent pending

Bluetooth is a trademark of Bluetooth SIG, Inc., USA

❑ Customized displays:

- Numeric: $3\frac{1}{2}$ digits, for the indication of position or torque
- Graphic: 32x122 dots, for a complete diagnostic user-friendly communication with the operator
- Backlights
- Heater
- 5 selectable languages as standard

❑ A single enhanced-type terminal board

❑ Advanced open bus communication protocols:

- Lonworks
- Profibus DPV0, DPV1 and Redundant DPV1
- Foundation Fieldbus
- Modbus
- DeviceNet

Diagnostics

Internal circuits continuously monitor the status of the system and elaborate all the information coming from the sensors: diagnostic messages are displayed in one of the available languages, so that there is no need to decipher complicated codes.

The set of messages is complete both with alarms and warnings.



the new generation takes a step forward...

...in cost reduction and user-friendliness

The reduced number of mechanical parts ensures higher reliability and lower maintenance costs.

The aluminium alloy highly resistant housing and covers, together with a lower number of joints, have increased Icon capacity to stand up to the most aggressive environments.

A double-sealed enclosure assures protection from dust and humidity. The choice of internal components has increased the overall system efficiency (the motor is directly engaged to the gears) lowering the operational costs.

Reduction of training costs is also one of the goals we have achieved through the user-friendliness of the system.

No more codes to decipher: the Icon menu is clear and easy, and comes with all the following languages: Italian, English, Spanish, Portuguese, French.

Internal sensors

All internal sensors are contactless.

Torque sensor

The direct measure of the motor speed reports torque with high precision and a resolution of 1% of the nominal torque. Torque detection is based on motor torque vs. speed characteristics, voltage and temperature compensated. The torque vs. speed curve is memorised for each type of motors and in case of motor replacement simply a new configuration from the actuator local control panel is requested.

Position sensor (US Patented)

Controlled by a dedicated microprocessor with low power consumption, the contactless position sensor is based on Hall-effect incremental encoder with a resolution of 10° of output shaft rotation.

Rotations in both senses are recognised and counted.

If manually operated during power failure, the position is updated, stored and displayed locally.

Electronic card: the latest technology

The card is controlled by a Hitachi high-performance 16-bit microchip, with a 4 Mb flash memory.

This allows high flexibility and the possibility to be re-programmed if necessary.

The internal wiring is considerably reduced.

The modular design of the electronic cards allows high flexibility for a great variety of combinations.



ICON 2000v4 software: PC and PDA manager

Model ☒ Operation ☐ Tools



Actuator Setup ☐ Name Plate
Valve Data ☒ Maintenance

A dedicated software for PC and PDA is available for ICON 2000v4.

With the new software, total control of ICON 2000v4 is always available in your hands and in your office.

With a smart user-friendly graphic interface, all the actuator information, set-up, configuration data, diagnostic messages and data logger info are available for visualisation, analysis and reconfiguration from your PDA or PC.



PDA Manager


The PDA Manager will transform your common PDA or dedicated industrial PDA into a strong tool for the complete control, set-up and diagnostics of the ICON 2000v4 actuators installed in your plant.

A user-friendly graphic interface reproduces the actuator local control panel for an easy control of the valve and offers several tools for a complete analysis of the actuator status.

ICON 2000v4 supports Bluetooth™ and IrDA non-intrusive communication.

In particular, with Bluetooth™ communication it is possible to communicate with the actuator within a distance of several meters from any angle.


In addition, it is possible to connect to all the actuators within operation distance with one single PDA.



Actuator data

Actuator set-up


Valve data



Actuator control



Maintenance tools



The PDA Manager software supports Bluetooth™, USB and IrDA communication (Windows 2000 and XP operating systems).

All the data exchanged with the actuator on-field can be shared with your PC in the office through the PC Manager Software.

Connect the PDA to the PC with the ActiveSync program and download all the data.

Standard PDA minimum basic requirements:

- ☐ Operating systems: Windows, Mobile™ 2003 for Pocket PC;
- ☐ Bluetooth™ interface module;
- ☐ Processor: 266 MHz processor;
- ☐ Memory: 32 MB SDRAM minimum;
- ☐ 3.5" TFT display with 16k colour depth.

Ex-hazardous area industrial PDA technical characteristics:

- High performance industrial PDA based on Windows, Mobile™, with compact external dimensions, an integrated WLAN, USB and Bluetooth™ port.
- Meets different industry requirements operating both inside and outside of Ex-hazardous areas.

Basic features:

- ☐ Ergonomic design to facilitate operations without fatigue during continuous use;
- ☐ High resolution colour display, readable even in the most unfavourable light conditions;
- ☐ Protection from static electricity, water and dust;
- ☐ Shockproof housing (non-corroding);
- ☐ Standard keyboard with navigation field and programmable keys;
- ☐ 3.5" TFT display with 16k colour depth.

Technical data sheet:

- ☐ Operating systems: Windows, Mobile™ 2003 Premium-Software for Pocket PC;
- ☐ Processor: 400 MHz processor based on Intel technology;
- ☐ Power supply: Rechargeable battery;
- ☐ Standard delivery: Unit, Charger, Operating instructions, safety instruction, software CD;
- ☐ Ex-Data:
 - Ex-hazardous application intrinsically safe type and suitable for different gas and dust atmospheres, ATEX or other certification.



ICON 2000v4 software: PC and PDA manager




PC Manager

PC Manager transforms your PC into a strong tool for the control, set-up and diagnostics of ICON 2000v4 actuators.

A user-friendly graphic interface reproduces the actuator local control panel for an easy control of the valve and offers several tools for a complete analysis of the actuator status.

ICON 2000v4 supports Bluetooth™ and IrDA non-intrusive communication or serial communication (intrusive).




The same interfaces available with PDA MANAGER with an improved graphic release (considering the larger screens available on PCs) are easily synchronisable with the PDA:

- Actuator control:




- Actuator maintenance and diagnostic informations:



- Actuator set-up:




- Actuator data logger:



PC Manager software supports Bluetooth™, USB and IrDA communication (Windows 2000 and XP operating systems).




**Double sealed terminal box for high protection.
Wide enclosure to facilitate wiring connection**




Easy connection for quick motor removal

**Heavy-duty simplified
gearing for higher efficiency**



**High precision internal sensors.
Low consumption position
encoder specifically designed
for electric actuators**



**User friendly interface:
actuating your valve has
never been so easy**



**Recessed buttons
for better protection**





base version features

The base version is an intelligent actuator with hardwired (i.e. point-to-point) connection.

High profile standards: all major features are included in the base version.

Automatic phase correction

The valve will be protected as the system automatically recognises and corrects phases preventing any unforeseen error in the rotation direction.

Phase failure correction

In case of loss of one phase, this feature prevents the motor from overheating. The minimum time to set the alarm on is 100 ms, in order to prevent the system from being influenced by casual oscillations. In case of loss of one phase during motor running, the actuator will reach the end-of-travel position before setting the alarm condition and de-energising the actuator.

Motor thermostat

If during operation the temperature of the motor overrides the security limits, a thermostat will set the alarm condition and the command signal will be inhibited.

Jammed valve protection

If, after a command (close/open), the valve position does not change within a pre-set time, an alarm condition is set and the command signal will be inhibited. The pre-set time can be any time within an interval of 2 to 100 seconds.

Anti-hammer protection

This feature will protect both the motor and the valve. If a torque limit is reached it will prevent the valve from moving in the same direction which caused the torque limit.

Instantaneous reversal protection

When the actuator is operating in one direction and an immediate command for a reverse direction is set, unpredicted current surges arise with possible damages to the motor. To prevent such problems, a delay between the opposite commands can be programmed from 500 ms to 5 seconds.

Warnings

Warning signals become active when the operating conditions are close to a critical alarm level. Warning is displayed but operation is not interrupted.

Remote controls

Three different configurations are available:

- 4 wires (OP, CL, Stop, C/latched)
- 3 wires (OP, CL, C/push-to-run or latched with instant reverse)
- 2 wires (NO contact to open or reverse)

Control voltage

- 24Vdc, internal supply
- 20 to 125 Vdc, external supply
- 20 to 120 Vac, external supply

Remote output contacts

Nine voltage-free latching contacts are available for remote indication.

They can all be configured as Normally Open or Normally

Closed for one of the following conditions:

- Fully open
- Fully closed
- Intermediate position
- Position \geq XX %
- Position \leq XX %
- Actuator opening
- Actuator closing
- Motor running
- Blinker
- Local selected
- Remote selected
- Local stop active
- ESD active
- Manual operation
- Motor over temperature
- Torque alarm
- Torque alarm in opening
- Torque alarm in closing
- Jammed valve alarm
- Jammed valve in opening
- Jammed valve in closing
- Mid-travel alarm
- Warning
- Low battery

Emergency shutdown (ESD)

When an ESD signal is received (in an emergency situation), the actuator performs the ESD programmed action. It can be configured to override any of the following conditions:

- Selector in LOCAL
- Selector in OFF
- Motor temperature alarm
- Local STOP pushbutton
- Torque alarm
- 2 speed timer

and it can be programmed to one of the following:

- Stay put
- Move to open position
- Move to close position
- Move to pre-set position

Monitor relay

When the actuator is not available for remote control, an alarm condition is set. The contact type is change-over, voltage-free. The monitor relay is normally energized and will be de-energized on:

- Loss of power
- Electrical contactor failure
- Internal temperature alarm
- Position sensor
- Speed sensor
- Configuration error
- Hardware error
- Mid-travel alarm

The following conditions can be individually configured to switch over the monitor relay:

- Loss of one phase
- Local stop activated
- Local selector switch in LOCAL/OFF
- Motor temperature alarm
- Torque alarm
- Jammed valve
- Manual operation
- ESD signal
- Low battery

Contactor failure

As one of the vital parts of the actuators, contactors are continuously monitored. If a malfunction is detected an alarm is set and the command is inhibited.

Maximum torque alarm

During torque operation, if the current torque exceeds the relevant set value, the actuator command is inhibited and an alarm condition is set.

Opto-coupled remote controls

Actuator may be remotely controlled by 4, 3 or 2 wires, depending on the connection on the terminal board. Several options are available: latched, momentary, etc...

Torque alarm by-pass

During opening command, starting from open/closed position it is possible to set an interval from 0% to 20% of the total stroke where torque alarm is ignored.

This will allow the actuator to win the Break-to-open torque.

High/Low electronic temperature

Through a semiconductor-based temperature sensor, the temperature in the electronic card is detected and an alarm condition is set on reaching the lowest/highest limits.

base version features



Local operator interface

The local interface is designed for easy operation and to supply a complete and clear set of information.

It is composed of

- a padlockable three-position selector for LOCAL/OFF/REMOTE operation selection
- three pushbuttons for local OPEN/CLOSE/STOP controls and menu navigation
- 2 customised displays, with backlight and heater:
 - numeric 3½ digit display for torque and position indication
 - graphic display supporting various character sets

All buttons are recessed for protection from accidents or misuse. The local push-buttons OPEN/CLOSE can be configured with 3 options: latched, latched + instant reverse, or push-to-run.

Through the local interface the field operator can enter a basic configuration menu which allows to set the following parameters:

Base parameters

- End of travel position in opening/closing
- Opening/closing torque values
- Position/torque display
- Opening/closing by torque/position
- Output contacts
- ESD feature
- Remote/Local control feature

Extended parameters

- Timer parameters
- Position servo-amplifier parameters
- Fieldbus interface parameters
- Data logger
- Maintenance date
- Diagnostic info
- PID parameters
-

The configuration menu is password-protected.

Three LEDs with settable different colours to indicate valve opening/closing, alarms, warnings, mid-travel and end-of-the-stroke positions.

Added extra features

Predictive maintenance

Some of the most vital parts of the actuator are monitored:

- contactor cycles count
- torque trend
- alarms data log

Timer Function Module (TMR)

It allows for partial or complete timer controlled valve stroke. Through the local/remote interface the following can be set:

- if it has to be active during opening or closing operation
- ON time, from 2 to 200 sec max, with resolution of 1 sec.
- OFF time, from 1 to 200 sec max, with resolution of 1 sec.
- percentage of position when timer starts in opening
- percentage of position when timer starts in closing

Electronic card identification message

Base, terminal board and 4-20mA card are clearly identified with a 64 character message for fast track including:

- Biffi assembly code
- Assembly serial number
- Manufacturing date
- Software and Hardware versions
- Description

Data log

ICON2000 is complete with an exhaustive data log system which will allow for storage of main events occurring during actuator operation. The monitored data are:

Alarms:

- ☐ Last 5 alarms and date
- ☐ Last 5 warnings and date

Torque profiles:

- ☐ Breakout reference torque in opening
- ☐ Peak running reference torque in opening
- ☐ Ending reference torque in opening
- ☐ Breakout torque in opening
- ☐ Peak running torque in opening
- ☐ Ending torque in opening
- ☐ Breakout reference torque in closing
- ☐ Peak running reference torque in closing
- ☐ Ending reference torque in closing
- ☐ Breakout torque in closing
- ☐ Peak running torque in closing
- ☐ Ending torque in closing
- ☐ Date of the last "set torque reference"
- ☐ Date of last torque profile in opening
- ☐ Date of last torque profile in closing

Operations:

- ☐ Opening time of the last stroke
- ☐ Closing time of last stroke
- ☐ Total contactor operations
- ☐ Motor run time
- ☐ Time out without electrical power
- ☐ Utilisation rate
- ☐ Recent contactor operations
- ☐ Recent motor run time
- ☐ Recent time without electrical power
- ☐ Recent utilisation rate

Maintenance data:

- ☐ Last maintenance date
- ☐ Next maintenance date
- ☐ Date of the last "clear recent data log"
- ☐ Start-up date

Name plate

The basic information about the actuator are electronically stored in a non-volatile memory:

- ☐ Serial number
- ☐ Actuator size
- ☐ Nominal torque
- ☐ Actuator speed
- ☐ Power supply
- ☐ Motor rating
- ☐ Motor duty
- ☐ Motor poles
- ☐ Motor type
- ☐ Motor current
- ☐ Test date
- ☐ Wiring diagram
- ☐ Enclosure
- ☐ Certificate
- ☐ Lubricant
- ☐ HW version
- ☐ SW version

Valve data

To identify the valve and its function in the process, the valve manufacturer/end user can enter the following data:

- ☐ valve tag name
- ☐ valve serial number

28 characters are available for such information.

Customisable torque profiles

In some applications you need to set different torque profiles for operating the valve.

For this reason we have introduced a 3-point torque profile.

Sleep mode function (for DC models only)

A specific sleep mode function is set up for DC actuators in order to save power available in the plant. All functionalities are kept in stand-by mode when not requested and immediately available on demand.



base version technical data

The following is a description of our ICON2000 standard features/options and working conditions.
For whatever you may require which is not listed below, please contact Biffi Sales offices.

Voltage ratings

The actuator can accept the following voltage supplies:

Three phase:

- | | |
|--|--------------------------------|
| <input type="checkbox"/> 50 Hz | <input type="checkbox"/> 60 Hz |
| 230, 240, 380, 400, 415, 440, 460, 480, 500, 690 V | 208, 280, 380, 460, 480, 575 V |

Single phase

- ☐ 110, 115, 220, 240 V at 50, 60 Hz

Direct Current

- ☐ 24, 48, 110, 240 V

Tolerance on fluctuations

- | | |
|---|---|
| <input type="checkbox"/> Voltage: $\pm 10\%$ continuous
+10% -15% intermittent | <input type="checkbox"/> Frequency: $\pm 2\%$ |
|---|---|

Working temperature

- ☐ The standard range is -30°C to $+85^{\circ}\text{C}$
- ☐ Extended ranges -40°C to $+65^{\circ}\text{C}$
- ☐ Special low range temperature version -55°C to $+65^{\circ}\text{C}$

Storage temperature

- ☐ From -55°C to $+85^{\circ}\text{C}$

Environmental protections

- ☐ **Only waterproof**
IP 68 according to IEC 529 and CEI EN60529 (15 m dept/90 hours), or alternatively
NEMA 4, NEMA 4X and NEMA 6 according to NEMA ICS6
- ☐ **Standard explosionproof degree**
Ex-d IIB T4 according to EN50014, EN50018 and EN50281-1-1 ($-55^{\circ}\text{C}/+85^{\circ}\text{C}$)
IP 68 according to IEC 529 and CEI EN60529 (15 m dept/90 hours), or alternatively
NEMA 4, NEMA 4X and NEMA 6 according to NEMA ICS6
- ☐ **Optional explosionproof degree**
 1. Ex-de IIB T4 according to EN50014, EN50018, EN50019 and EN50281-1-1
Working temperature range: -25°C to $+65^{\circ}\text{C}$
IP 68 according to IEC 529 and CEI EN60529 (15 m dept/90 hours), or alternatively
NEMA 4, NEMA 4X and NEMA 6 according to NEMA ICS6
 2. Ex-d IIC T4 ($-25^{\circ}\text{C}/+65^{\circ}\text{C}$) (consult factory)
Ex-de IIC T4 ($-25^{\circ}\text{C}/+65^{\circ}\text{C}$) (consult factory)
Ex-de IIB +H₂ T4 ($-25^{\circ}\text{C}/+65^{\circ}\text{C}$) (consult factory)
IP 68 according to IEC 529 and CEI EN60529 (15 m dept/90 hours), or alternatively
NEMA 4, NEMA 4X and NEMA 6 according to NEMA ICS6



3. US/Canada Standards:

- FM/CSA Class I, Division 1, Groups C and D
- Class II, Division 1, Groups E, F and G
- Class III, Division 1, Groups E, F and G
- Temperature classes: T4A, -55°C to +60°C
- T4, -55°C to +70°C
- NEMA 4, 4X and 6

Safety Compliance

☐ Electromagnetic compatibility directive (EMC)

ICON2000 actuators conform to the requirements of EMC Directive **89/336/EEC** and further amendments.

☐ Low voltage directive (LV)

ICON2000 actuators conform with Low Voltage Directive **73/23/EEC** and further amendments by the application of **EN60204-1 1993**.

☐ Machinery directive

ICON2000 actuators comply with the provision of Machinery Directive **98/37/EEC**.

☐ ATEX directive (94/9/EEC)

ICON2000 v4 actuators are certified according to Ex II 2 GD.

Test Summary

☐ Life test

Standard ICON2000 life test is based on **AWWA 540-93** for a minimum of 10,000 cycles.

☐ Vibration test

ICON2000 are certified as per **IEC 60068-2-6- Appendix B** (plant induced): frequencies from 1 to 500 Hz (in 3 axes) with 2.0g peak acceleration. Sweep cycles in each axis: 10.

☐ Seismic test

ICON2000 are tested in accordance with **IEC 60068-2-57**. Frequencies from 1 to 35 Hz (in 3 axes) with max 2.0g peak acceleration. Verification of structural integrity at 5g. Endurance of oscillogram: 30 seconds.

☐ Environmental test

ICON2000 are tested according to the following standards: **IEC 68-2-1** (cold) up to -55°C, **IEC 68-2-2** (dry heat) up to +85°C, **IEC 68-2-3** (damp heat) up to +40°C with 93% relative humidity.

☐ Salt spray test

ICON2000 external coating is tested for resistance to salt spray for 1,500 hours according to **ASTM B117/IEC 68-2-11**.

☐ Noise test

ICON2000 are tested according to **EN21680**. Noise level is less than 65 dB (grade A) at 1m distance.

Motors

Base version ICON2000 are equipped with three-phase asynchronous, squirrel cage, induction-type low-inertia balanced motors. For single phase or direct current supply, a special interface allows to use conventional asynchronous motors. The open frame is protected by an Explosionproof / Waterproof cover fixed on the actuator housing. Internal protection by a temperature sensor, inserted in the motor windings. The motor flange is directly coupled to the actuator housing with internal flying leads wired to an intermediate terminal board. Electric motors are supplied with insulation class H as standard with dedicated speed and temperature sensor.

Cinematic reduction chain and lubrication

Motor power is transmitted to the output hollow shaft directly via a high torque capability and high efficiency worm shaft/worm wheel reduction without any interposition of spur or helical gears. Output hollow shaft is with teeth termination in order to transmit only a torque to the stem nut.

Lubrication is through oil bath (two oil plugs are provided for filling and draining).

base version technical data

Manual override

All actuators are provided with a handwheel for manual operation. The de-clutching mechanism is designed so that motor operation always has priority over manual operation. Whenever the motor is started, the hand mechanism will automatically disengage without engaging the operator. The de-clutch lever is padlockable in two positions (only electrical or only manual) to prevent undesired operation.

Terminal block

Terminal block is located in a double sealed enclosure.

The terminal block is provided with the following terminations and accessories:

- 3 terminals for power supply
- 46 terminals for controls
- 2 for DC external supply
- 2 for low voltage (max 230V) external supply
- 1 external earth
- 1 external neutral

Cable entries

Three cable entries are supplied as standard.

One extra entry is optionally available.

The standard thread is NPT and diameter is:

- one with 1 1/2"
- two with 1"
- one with 3/4" (optional)

ISO Rc 7/1, ISO metric BS3643 and DIN 40430/PG and different diameters are available as options.

Data logger

"Data logger" is available for collecting different types of data useful in maintenance or diagnostic programs. Since the amount of collected data is quite large, the data logger must be downloaded onto a Pc/Pda through Irda or Bluetooth™ connection to be viewed.

The main functions of the Data logger are:

- RECORDER mode: measurement and memorisation of main voltage supply (V), motor temperature (C°), electronics compartment temperature (C°), with configurable sampling time and start date and time (up to 256 sets of measures can be memorised)
- EVENT mode: memorisation of Open or Close commands, with indication of source, date and time. Configurable Start date and time. Up to 128 events can be memorised.





optional modules

*A large variety of optional modules can be added to the base version.
If the option you are looking for is not listed below, please contact Biffi.*

Fieldbus interfaces

ICON2000 modular design is easily upgraded from base-to-base to bus versions. You just need to add the relevant plug-in card.

ICON2000 flexible interface allows connection to the major field bus available on the market:

Foundation Fieldbus

Profibus DPV0, DPV1 and redundant DPV1

LonWorks

DeviceNet

Modbus

...

Please ask our Sales people for specific requirements.

Position Servoamplifier Module (PSM)

The module is necessary for actuators in modulating and inching duty. It drives the motor through pulses at constant frequency and duration proportional to the position error, following an externally set analogical point signal.

The basic features are:

Input: 4-20 mA or 0-20 mA with galvanic insulation

Output: 4-20 mA with galvanic insulation for position or torque re-transmission.

Three additional SPST output contacts to be configured "make or break".

2 interlock inputs.

Position Analogue Retransmission Module (APTm)

This card gives a 4-20 mA galvanically insulated module for position or torque retransmission. It is easily plugged in on the base card with no need for dedicated tools.

Torque/position Analog Retransmission Module (ATTm)

Same as APTm but with two 4-20 mA galvanically insulated modules for position and torque retransmission.

PID module

This module is useful when a closed loop control of a process variable is requested.

It can receive an analogue signal from a transducer and drive the actuator to maintain the desired set-point value of the parameter (temperature, pressure, flow).

Solid state power switch over temperature

(only for heavy modulation duty version)

It detects power card maximum temperature condition and sets the relevant alarm.

Extended temperature ranges

-40/+70 °C by use of extended range components

-55/+70 °C by use of a heating source for internal electronic components, powered by external supply.

Anticondensate heater

The internal modules provide enough power to grant anticondensation protection for general applications. But when the environment air humidity reaches critical levels, an additional heater (10 Watt - 1500 Ohm, with **external power supply**) may be supplied on request.

Battery

Auxiliary batteries can be provided in an **intrinsically safe enclosure**. With auxiliary batteries it is possible to remotely transmit position also in case of power failure.

Handwheel with reduction gearing

Side-mounted handwheel with additional reduction, with engagement lever. The reduction on the manual operation reduces the torque at the handwheel. This provides less "rim-pull" force for the operator. The following ratios are applicable:

model	ratio
030	10:1
040	13:1
050	17:1


Special couplings

To be able to cope with different applications and working condition, two special couplings are available:


- The **linear coupling** was designed for the motorization of valves with stem linear movement and no anti-rotational devices on the stem (e.g. application on modulating globe valves). This type of coupling converts multi-turn actuator rotational motion into linear motion: in this way the motorization is extremely simple and compact.
- **Spring-compensated coupling** ASC type. The spring coupling block has its best application on actuators for wedge and globe valves working at high temperatures. The trim of valves working at temperatures higher than 450°C and subjected to large temperature changes undergoes expansions and contractions that are very dangerous to the valve and to the actuator thrust coupling. If, on the other hand, low temperatures are causing contractions, valve unseating could occur. The spring-compensated coupling is designed to cope with both high and low temperatures: the spring cups allows the stem nut to move axially. The same coupling can also be used in case of high speeds, as the springs reduce the over-strokes effects by absorbing the kinetic energy.




tables and drawings*




Model 010



Models 020/030/040/050





Lever Position Detail




Standard cable entries:
a = 1" NPT
b = 1 1/2" NPT

ICON2000 Series Overall Dimensions

Model	A	a1	a2	B	b1	b2	ØC	F	H	h1	h2	h3	Mass Kg
ICON-010	485	325	160	565	273	292	300	F10	324	142	152	210	32
ICON-020	597	347	160	583	283	300	500	F14	374	161	161	240	45
ICON-030	699	399	160	625	313	312	600	F14	431	185	175	270	70
ICON-040	815	455	170	690	318	372	720	F16	478	196	191	291	86
ICON-050	938	508	180	755	363	392	860	F25	549	223	218	336	110



Lever Position Detail



Standard cable entries:
a = 1" NPT
b = 1 1/2" NPT

ICON2000 Series Overall Dimensions (with reduced manual override)

Model	A	a1	a2	B	b1	b2	ØC	F	H	h1	h2	h3	Mass Kg
ICON-030	648	399	249	625	313	312	300	F14	486	171	182	263	78
ICON-040	723	455	268	690	318	372	400	F16	558	196	191	284	94
ICON-050	779	508	271	755	363	392	500	F25	693	223	218	336	118

Notes

1. The ** are to be replaced by RPM value at selected frequency (50 or 60 Hz)
2. Nominal output torque settable from 40% (minimum torque) to 100% of indicated value
3. Theoric max output torque. The actual max output torque is a function of speed and motor power supply and may vary from 1.4 to 2 times the nominal output torque
4. The above performances are referred to ON/OFF S2-15' or INCHING S4-25%-60 starts/hour duties (IEC34-1)
5. Referred to Running torque = 40% Nominal torque

Multiturn Actuator Performances with 3-phase motors ⁽⁴⁾ - ON/OFF or Inching service


Model ⁽¹⁾	Nom. Torque ⁽²⁾ (100%) (Nm)	Min. Torque (Nm)	Max. Torque ⁽³⁾ (Nm)	RPM ⁽⁵⁾ (50 Hz)	RPM ⁽⁵⁾ (60 Hz)	Motor Type	Motor Power (KW) at 50 Hz	Motor Power (KW) at 60 Hz	R
ICON-010/30-**-	30	12	45	12	14	SM00	0.030	0.036	40:1
ICON-010/30-**-	30	12	45	18	22	SM01	0.046	0.055	40:1
ICON-010/30-**-	30	12	45	24	29	SM10	0.071	0.085	20:1
ICON-010/30-**-	30	12	45	36	43	SM11	0.106	0.127	20:1
ICON-010/30-**-	30	12	45	48	58	SM04	0.142	0.170	20:1
ICON-010/30-**-	30	12	45	72	86	SM05	0.213	0.256	20:1
ICON-010/30-**-	30	12	45	144	173	SM06	0.426	0.511	20:1
ICON-010/90-**-	90	36	135	12	14	SM10	0.071	0.085	40:1
ICON-010/90-**-	90	36	135	18	22	SM11	0.106	0.127	40:1
ICON-010/90-**-	90	36	135	24	29	SM12	0.122	0.146	20:1
ICON-010/90-**-	90	36	135	36	43	SM13	0.184	0.221	20:1
ICON-010/90-**-	90	36	135	48	58	SM14	0.286	0.343	20:1
ICON-010/90-**-	90	36	135	72	86	SM15	0.367	0.440	20:1
ICON-010/90-**-	90	36	135	144	173	SM16	0.735	0.882	20:1
ICON-020/180-**-	180	72	270	12	14	SM12	0.122	0.146	40:1
ICON-020/180-**-	180	72	270	18	22	SM13	0.184	0.221	40:1
ICON-020/180-**-	180	72	270	24	29	SM14	0.286	0.343	40:1
ICON-020/180-**-	180	72	270	36	43	SM15	0.367	0.440	40:1
ICON-020/180-**-	180	72	270	48	58	SM21	0.526	0.631	20:1
ICON-020/180-**-	180	72	270	72	86	SM22	0.789	0.947	20:1
ICON-020/180-**-	180	72	270	144	173	SM23	1.470	1.764	20:1
ICON-030/360-**-	360	144	540	12	14	SM21	0.526	0.631	80:1
ICON-030/360-**-	360	144	540	18	22	SM32	0.500	0.600	40:1
ICON-030/360-**-	360	144	540	24	29	SM21	0.526	0.631	40:1
ICON-030/360-**-	360	144	540	36	43	SM22	0.789	0.947	40:1
ICON-030/360-**-	360	144	540	48	58	SM30	1.123	1.348	20:1
ICON-030/360-**-	360	144	540	72	86	SM23	1.470	1.764	40:1
ICON-030/360-**-	360	144	540	144	173	SM31	3.368	4.042	20:1
ICON-040/720-**-	720	288	1080	12	14	SM30	1.123	1.348	80:1
ICON-040/720-**-	720	288	1080	18	22	SM44	0.840	1.008	40:1
ICON-040/720-**-	720	288	1080	24	29	SM30	1.123	1.348	40:1
ICON-040/720-**-	720	288	1080	36	43	SM40	1.684	2.021	40:1
ICON-040/720-**-	720	288	1080	48	58	SM41	1.939	2.327	20:1
ICON-040/720-**-	720	288	1080	72	86	SM31	3.368	4.042	40:1
ICON-040/720-**-	720	288	1080	144	173	SM42	5.818	6.982	20:1
ICON-050/1440-**-	1440	576	2160	12	14	SM41	1.939	2.327	80:1
ICON-050/1440-**-	1440	576	2160	18	22	SM40	1.684	2.021	80:1
ICON-050/1440-**-	1440	576	2160	24	29	SM41	1.939	2.327	40:1
ICON-050/1440-**-	1440	576	2160	36	43	SM43	2.885	3.462	40:1
ICON-050/1440-**-	1440	576	2160	48	58	SM50	3.879	4.655	20:1
ICON-050/1440-**-	1440	576	2160	72	86	SM42	5.818	6.982	40:1
ICON-050/1440-**-	1440	576	2160	144	173	SM51	11.636	13.963	20:1

Notes

1. The ** are to be replaced by RPM value at selected frequency (50 or 60 Hz)
2. Nominal output torque settable from 40% (minimum torque) to 100% of indicated value
3. Theoric max output torque. The actual max output torque is a function of speed and motor power supply and may vary from 1.4 to 2 times the nominal output torque
4. The above performances are referred to ON/OFF S2-30' or MODULATING S4-25%-600 starts/hour duties (IEC34-1)
5. Referred to Running torque = 40% Nominal torque
6. Ambient temperature from -55°C to 65°C

Multiturn Actuator Performances with 3-phase motors ⁽⁴⁾ - Modulating service


Model ⁽¹⁾	Nom. Torque ⁽²⁾ (100%) (Nm)	Min. Torque (Nm)	Max. Torque ⁽³⁾ (Nm)	RPM ⁽⁶⁾ (50 Hz)	RPM ⁽⁵⁾ (60 Hz)	Motor Type	Motor Power (KW) at 50 Hz	Motor Power (KW) at 60 Hz	R
ICON-010/30-**-	30	12	45	12	14	TM00	0.030	0.036	40:1
ICON-010/30-**-	30	12	45	18	22	TM01	0.046	0.055	40:1
ICON-010/30-**-	30	12	45	24	29	TM10	0.071	0.085	20:1
ICON-010/30-**-	30	12	45	36	43	TM11	0.106	0.127	20:1
ICON-010/30-**-	30	12	45	48	58	TM04	0.142	0.170	20:1
ICON-010/30-**-	30	12	45	72	86	TM05	0.213	0.256	20:1
ICON-010/30-**-	30	12	45	144	173	TM06	0.426	0.511	20:1
ICON-010/90-**-	90	36	135	12	14	TM10	0.071	0.085	40:1
ICON-010/90-**-	90	36	135	18	22	TM11	0.106	0.127	40:1
ICON-010/90-**-	90	36	135	24	29	TM12	0.122	0.146	20:1
ICON-010/90-**-	90	36	135	36	43	TM13	0.184	0.221	20:1
ICON-010/90-**-	90	36	135	48	58	TM14	0.286	0.343	20:1
ICON-010/90-**-	90	36	135	72	86	TM15	0.367	0.440	20:1
ICON-010/90-**-	90	36	135	144	173	TM16	0.735	0.882	20:1
ICON-020/180-**-	180	72	270	12	14	TM12	0.122	0.146	40:1
ICON-020/180-**-	180	72	270	18	22	TM13	0.184	0.221	40:1
ICON-020/180-**-	180	72	270	24	29	TM14	0.286	0.343	40:1
ICON-020/180-**-	180	72	270	36	43	TM15	0.367	0.440	40:1
ICON-020/180-**-	180	72	270	48	58	TM21	0.526	0.631	20:1
ICON-020/180-**-	180	72	270	72	86	TM22	0.789	0.947	20:1
ICON-020/180-**-	180	72	270	144	173	TM23	1.470	1.764	20:1
ICON-030/360-**-	360	144	540	24	29	TM21	0.526	0.631	40:1
ICON-030/360-**-	360	144	540	36	43	TM22	0.789	0.947	40:1
ICON-030/360-**-	360	144	540	48	58	TM30	1.123	1.348	20:1
ICON-030/360-**-	360	144	540	72	86	TM23	1.470	1.764	40:1
ICON-030/360-**-	360	144	540	144	173	TM31	3.368	4.042	20:1
ICON-040/720-**-	720	288	1080	24	29	TM30	1.123	1.348	40:1
ICON-040/720-**-	720	288	1080	36	43	TM40	1.684	2.021	40:1
ICON-040/720-**-	720	288	1080	72	86	TM31	3.368	4.042	40:1



Notes to couplings type A

- $\varnothing d_6$ = Max threaded stem acceptance
 $\varnothing d_x$ = The maximum accepted diameter described by the key
 F_{nom} = The max thrust applicable to the ICON2000 block type "A" in **dynamic conditions** with torque control set at 100%
 F_{max} = The max thrust applicable to the ICON2000 block type "A" in **static conditions** with manual override or with motor in stall torque


Model	010	020	030	040	050
ISO 5210	F10	F14	F14	F16	F25
F_{nom} (KN)	40	100	150	180	300
F_{max} (KN)	60	150	225	270	450
$\varnothing d_1$	125	175	175	210	300
$\varnothing d_2 f8$	70	100	100	130	200
$\varnothing d_3$	102	140	140	165	254
$\varnothing d_4$	M10	M16	M16	M20	M16
$\varnothing d_5$	33	46	62	68	78
$\varnothing d_6 max$	32	45	60.5	65	77
$\varnothing d_6 not machined$	18	19	26	30	35
$\varnothing d_x max$	32	45	60.5	65	77
l_1	40	55	70	75	95
l_2	51	68	84	94	120
h_1	3	4	4	5	5
h_2	15	24	24	30	24
N	4	4	4	4	8
Mass (Kg)	2	8	8	15	28



Notes to couplings type B1/B2

- ϕd_7 = with standard keyway according to ISO 773
- ϕd_x = The maximum accepted diameter described by the key

Model	010	020	030	040	050
ISO 5210	F10	F14	F14	F16	F25
ϕd_5	33	46	62	68	78
B1 ϕd_7 H9	42	60	60	80	100
B2 ϕd_7 max	42	60	60	80	100
ϕd_x max	50	71	71	94	116
l_3	45	65	65	80	110
l_4	56	85	84	105	155
Mass (Kg)	2	7	7	14	26




Notes to couplings type B3/B4


- ϕd_{10} = with standard keyway according to ISO 773
- ϕd_x = The maximum accepted diameter described by the key

Model	010	020	030	040	050
ISO 5210	F10	F14	F14	F16	F25
B3 ϕd_{10} H9	20	30	30	40	50
B4 $\phi d_y \text{ max}$	22	32	46	50	58
ϕd_x	26	40	55	60	68
l_6	100	120	130	150	180
Mass (Kg)	1	6	6	12	20

block and terminals diagram

General Configuration






NOTES :

- 1) B1-B2 : Internally linked
- 2) C1 : +24 Vdc not regulated, max 4W.
- 3) Control signal levels: Minimum "ON" >20Vdc or 20Vac (50/60Hz)
Maximum "ON" <125 Vdc or 120Vac (50/60Hz)
Maximum "OFF" <3 Vdc or ac
Minimum signal duration > 500ms
Total current drawn for remote controls <25mA
Total current drawn for ESD controls <15mA
- 4) Monitor relay :
Voltage free, change-over contact- max voltage 250Vac or 30Vdc- max current 5A/min. voltage 5Vdc - min. current 10mA
See instruction manual to view or configure the switching conditions of relay
-E2/D1 contact is closed when to be configured condition occurs
- 5) AS1, AS2, AS3, AS4, AS5, AS6, AS7 : Voltage free contact -Max voltage 250Vac or 30Vdc- max current 5A
min voltage 5Vdc- min contact 10A contact can be configured to make or break on condition. See instruction manual to view or configure switching conditions of relays
- 6) AS8 : Voltage free, change-over contact- max voltage 250Vac or 30Vdc- max current 5A/min. voltage 5Vdc - min. current 10mA
See instruction manual to view or configure the switching conditions of relay
-C9/D8 contact is closed when to be configured condition occurs

See instruction handbook to configure options A1,A2,A3,B1,B2,B3.
For 4-20mA connections see MAN 618/5, optional modules PSM1 and APTM1.
Remote STOP control SP can be configured to perform the STOP action when the contact is open (break) or closed (make).



Option E1: Internal supply 24Vdc INTERLOCK active with closed or open contact (to be configured)
Option E2: External supply 20-125 Vdc or 20-120 Vac (50/60Hz) INTERLOCK active with closed or open contact (to be configured)
See instruction handbook to configure INTERLOCK signal type

Option D1: Internal supply 24Vdc ESD active with closed or open contact (to be configured)
Option D2: External supply 20-125 Vdc or 20-120 Vac (50/60Hz) ESD active with closed or open contact (to be configured)

See instruction manual to configure ESD signal type, ESD action and priority.
If customers wishes to have the thermostat by-passed during ESD operation, it should be noted that any certification for actuator enclosure in hazardous area will be invalidated.

LEGENDA	
M	= Three-phase motor
Th	= Motor thermostat
OP	= OPEN control
CL	= CLOSE control
SP	= STOP control
K1	= Opening/Closing contactor
K2	= Opening/Closing contactor

- 7) A1,A2,A3 : Internal supply 24Vdc
- 8) B1,B2,B3 : External supply 20-125Vdc or 20-120 Vac (50/60Hz)
- 9) Controls mode :
Option A1/B1 : 4 wires latched (SP configuration = BREAK)
Option A2/B2 : 3 wires push to run
Option A3/B3 : 3 wires latched with instant reverse
Option A3/B3 : 2 wires open contact opens
Option A3/B3 : 2 wires open contact closes
- 10) A/M Open : Remote/Auto Actuator control by 4-20mA input signal
A/M Closed : Remote/Man Actuator control by remote push-buttons




Bevel Gear Reducers

For application on valves when a side-mounted multiturn actuator is requested.
Penstocks are another typical application for this type of reducer.

BGR Multiturn Actuator Performances with 3-phase motors⁽⁴⁾

Model BGR ⁽¹⁾	Nom Torque ⁽²⁾ (100%) (Nm)	Min Torque (Nm)	Max Torque ⁽³⁾ (Nm)	RPM ⁽⁵⁾ (50 Hz)	RPM ⁽⁵⁾ (60 Hz)	Motor Type
BGR-3-010/360-**-**	360	144	540	5	6	SM12
BGR-3-010/360-**-**	360	144	540	8	10	SM13
BGR-3-010/360-**-**	360	144	540	11	13	SM14
BGR-3-010/360-**-**	360	144	540	16	19	SM15
BGR-3-010/360-**-**	360	144	540	32	38	SM16
BGR-7-020/720-**-**	720	288	1080	5	6	SM14
BGR-7-020/720-**-**	720	288	1080	8	10	SM15
BGR-7-020/720-**-**	720	288	1080	11	13	SM21
BGR-7-020/720-**-**	720	288	1080	16	19	SM22
BGR-7-020/720-**-**	720	288	1080	32	39	SM23
BGR-15-030/1440-**-**	1440	576	2160	5	6	SM21
BGR-15-030/1440-**-**	1440	576	2160	8	10	SM22
BGR-15-030/1440-**-**	1440	576	2160	11	13	SM30
BGR-15-030/1440-**-**	1440	576	2160	16	19	SM23
BGR-15-030/1440-**-**	1440	576	2160	32	39	SM31
BGR-30-040/2880-**-**	2880	1152	4320	5	6	SM30
BGR-30-040/2880-**-**	2880	1152	4320	8	10	SM40
BGR-30-040/2880-**-**	2880	1152	4320	11	13	SM41
BGR-30-040/2880-**-**	2880	1152	4320	16	19	SM31
BGR-30-040/2880-**-**	2880	1152	4320	32	38	SM42
BGR-60-050/5760-**-**	5760	2304	8640	5	6	SM41
BGR-60-050/5760-**-**	5760	2304	8640	8	10	SM31
BGR-60-050/5760-**-**	5760	2304	8640	11	13	SM50
BGR-60-050/5760-**-**	5760	2304	8640	16	19	SM42
BGR-60-050/5760-**-**	5760	2304	8640	32	38	SM51

See notes for Multiturn Actuator Performances



Notes to couplings type A

Type "A" = The block having the capability to transmit both a torque and a thrust.

Ø d_x = The max accepted diameter described by the key

l₁ x 1.10 = Minimum threaded valve stem protusion

F_{nom} = The max thrust applicable to the BGR block type "A" in **dynamic conditions** with torque control set at 100%

F_{max} = The max thrust applicable to the BGR block type "A" in **static conditions** with manual override or with motor in stall torque

ICON2000 Series BGR

Dimension	BGR 3	BGR 7	BGR 15	BGR 30	BGR 60
ISO 5210	F14	F16	F25	F30	F35
F _{nom} (KN)	150	180	300	440	700
F _{max} (KN)	225	270	450	660	1050
Ø d ₁	175	210	300	350	415
Ø d ₂ f8	100	130	200	230	260
Ø d ₃	140	165	254	298	356
Ø d ₄	M16	M20	M16	22	33
Ø d ₅	62	68	78	78	97
Ø d ₆ max (d _x)	60.5	65	77	77	96
Ø d ₆ min	-	-	-	51	55
l ₁	70	75	95	110	144
l ₂	84	94	120	134	172
h ₁	4	5	5	5	5
h ₂	24	30	24	30	40
N	4	4	8	8	8
Mass (Kg)	8	15	28	48	75



Spur Gear Reducers

For application on valves when a multiturn actuator is required and torque exceeds 1440 Nm.

The spur gear reducer and its thrust block are designed for the severest duties.

SGR Multiturn Actuator Performances with 3-phase motors⁽⁴⁾

Model SGR ⁽¹⁾	Nom Torque ⁽²⁾ (100%) (Nm)	Min Torque (Nm)	Max Torque ⁽³⁾ (Nm)	RPM ⁽⁵⁾ (50 Hz)	RPM ⁽⁵⁾ (60 Hz)	Motor Type
SGR-160-030/1750-**-	1750	700	2625	26	31	SM31
SGR-160-030/2150-**-	2150	860	3225	21	26	SM31
SGR-160-030/2880-**-	2880	1152	4320	8	10	SM23
SGR-160-030/2880-**-	2880	1152	4320	16	19	SM31
SGR-250-030/3600-**-	3600	1440	5400	12	15	SM31
SGR-250-040/3600-**-	3600	1440	5400	24	29	SM42
SGR-250-030/4800-**-	4800	1920	7200	5	6	SM23
SGR-250-030/4800-**-	4800	1920	7200	9	11	SM31
SGR-250-040/4800-**-	4800	1920	7200	18	22	SM42
SGR-250-050/4800-**-	4800	1920	7200	36	43	SM51
SGR-400-030/7500-**-	7500	3000	11250	6	7	SM31
SGR-400-040/7500-**-	7500	3000	11250	12	14	SM42
SGR-400-050/7500-**-	7500	3000	11250	24	29	SM51
SGR-400-040/9600-**-	9600	3840	14400	5	6	SM21
SGR-400-040/9600-**-	9600	3840	14400	9	11	SM42
SGR-400-050/9600-**-	9600	3840	14400	18	22	SM51
SGR-640-050/9600-**-	9600	3840	14400	18	22	SM51
SGR-640-040/15000-**-	15000	6000	22500	6	7	SM42
SGR-640-050/16000-**-	16000	6400	24000	11	13	SM51
SGR-640-050/19200-**-	19200	7680	28800	5	6	SM42
SGR-640-050/19200-**-	19200	7680	28800	9	11	SM51
SGR-1000-050/22000-**-	22000	8800	33000	8	9	SM51
SGR-1000-050/28000-**-	28000	11200	42000	6	7	SM51
SGR-1000-050/37000-**-	37000	14800	55500	2	3	SM42
SGR-1000-050/37000-**-	37000	14800	55500	5	6	SM51
SGR-1600-050/40000-**-	40000	16000	60000	4	5	SM51
SGR-1600-050/48000-**-	48000	19200	72000	3	4	SM51
SGR-1600-050/57000-**-	57000	22800	85500	3	4	SM51

See notes for Multiturn Actuator Performances

Notes to couplings type A

Type "A" = The block having the capability to transmit both a torque and a thrust.



$\varnothing d_x$ = The max accepted diameter described by the key
 $l_1 \times 1.10$ = Minimum threaded valve stem protusion

F_{nom} = The max thrust applicable to the SGR block type "A" in **dynamic conditions** with torque control set at 100%


F_{max} = The max thrust applicable to the SGR block type "A" in **static conditions** with manual override or with motor in stall torque

ICON2000 Series SGR

Dimension	SGR 160	SGR 250	SGR 400	SGR 640	SGR 1000	SGR 1600
ISO 5210	F30	F35	F35	---	---	---
F_{nom} (KN)	440	700	1200	2250	3200	4500
F_{max} (KN)	660	1050	1800	3375	4800	6750
$\varnothing d_1$	350	415	415	475	500	620
$\varnothing d_2 f_8$	230	260	260	300	330	400
$\varnothing d_3$	298	356	356	406	425	520
$\varnothing d_4$	22	33	33	39	M36	M45
$\varnothing d_5$	78	97	109	130	156	188
$\varnothing d_{6 max} (d_x)$	77	96	108	127	153	180
$\varnothing d_{6 min}$	51	55	60	75	90	95
l_1	110	144	178	216	252	307
l_2	134	172	201	250	290	354
h_1	5	5	5	8	8	8
h_2	30	40	45	45	50	58
N	8	8	8	16	16	16
Mass (Kg)	48	75	105	150	195	250



Lever Position Detail





Standard cable entries:

a = 1" NPT


b = 1 1/2" NPT

SGR/ICON2000 Series Overall Dimensions

Model	A	a1	a2	a3	B	b1	b2	ØC	F	H	h1	h2	h3	Mass Kg
SGR-160-030	859	399	270	190	625	313	312	400	F30	617	231	380	251	127
SGR-250-030	927	399	319	227	625	313	312	500	F35	684	315	380	345	154
SGR-250-040	983	445	319	227	690	318	372	500	F35	724	280	420	310	170
SGR-250-050	1036	508	319	227	775	363	392	500	F35	684	280	380	310	194
SGR-400-030	980	399	373	208	625	313	312	500	F35	736	356	380	383	232
SGR-400-040	1036	455	373	208	690	318	372	500	F35	776	356	420	383	248
SGR-400-050	1089	508	373	208	755	363	392	500	F35	866	356	510	383	272
SGR-640-040	1098	455	405	237	690	318	372	600	SPEC.	838	418	420	460	288
SGR-640-050	1151	508	405	238	755	363	392	600	SPEC.	928	418	510	460	312
SGR-1000-050	1264	508	456	300	755	363	392	600	SPEC.	968	458	510	500	417
SGR-1600-050	1560	508	602	450	755	363	392	600	SPEC.	1040	522	510	564	752



Lever Position Detail



Standard cable entries:

a = 1" NPT

b = 1 1/2" NPT


SGR/ICON2000 Series Overall Dimensions (with reduced manual override)

Model	A	a1	a2	a3	B	b1	b2	ØC	H	h1	h2	h3	Mass Kg
SGR-160-030	814	354	270	190	679	300	379	300	717	231	486	251	135
SGR-250-030	880	354	319	227	678	302	376	300	748	315	448	345	162
SGR-250-040	942	416	319	227	742	310	432	400	828	280	528	310	178
SGR-250-050	1012	484	319	227	809	334	475	500	977	280	677	310	202
SGR-400-030	934	354	373	208	678	302	376	300	817	356	461	383	240
SGR-400-040	995	415	373	208	741	311	430	400	884	356	528	383	256
SGR-400-050	1064	484	373	208	809	334	475	500	1033	356	677	383	280
SGR-640-040	1057	415	405	238	743	311	432	400	947	418	528	460	296
SGR-640-050	1124	482	405	238	807	335	472	500	1091	418	673	460	320
SGR-1000-050	1240	484	456	300	809	334	475	500	1132	458	674	500	425
SGR-1600-050	1535	483	602	450	808	334	474	500	1196	522	674	564	760



Worm Gear Reducers for Quarter Turn Valves

For application on any type of quarter turn valves (ball, butterfly, plug...). The worm gear is designed to meet AWWA C-540 and other major standards.




Notes



1. Insert bush supplied by BIFFI with unmachined bore. Machining of bore upon request
2. Fixing bolts or rods supplied by BIFFI only on request, minimum material class required 8.8 UNI37409, ASTM A320-L7
3. Any other coupling can be supplied on request
4. Flanges for models WGR-800, 1600 and 3200 have double PCD.

ICON2000 Series WGR

Model	ISO 5211	Ø d ₁	Ø d ₃	Ø d ₄	N°	H	h ₂	Ø Pin	d ₇ Max Stem Acceptance	
									Insert Bush	
									Ø d ₇	Ø d ₄
WGR-100	F14	175	140	M16	4	100	16	16	42	51
WGR-200	F16	210	165	M20	4	105	20	16	65	76
WGR-400	F16	210	165	M20	4	105	20	16	65	76
WGR-800	F25	300	254	M16	8	115	20	20	90	104
WGR-800	F30	350	298	M20	8	115	20	20	90	104
WGR-1600	F25	300	254	M16	8	140	24	20	103	120
WGR-1600	F30	350	298	M20	8	140	30	20	103	120
WGR-3200	F30	350	298	M20	8	165	30	20	120	139
WGR-3200	F35	415	356	M30	8	165	30	20	120	139
WGR-6300	F40	475	406	M36	8	250	36	30	170	194



Lever Position Detail



Standard cable entries:

a = 1" NPT

b = 1 1/2" NPT

WGR/ICON2000 Series Overall Dimensions

Model	A	a1	a2	a3	B	b1	b2	ØC	D	F	H	h1	h2	Mass Kg
WGR-100-010	519	90	139	290	421	273	292	300	86	F14	387	62	115	40
WGR-200-010	560	123	147	290	466	273	292	300	119	F16	381	53	125	52
WGR-400-010	662	123	269	270	491	273	292	300	119	F16	390	53	125	69
WGR-800-020	820	150	302	368	562	283	300	500	130	F25	397	60	135	85
WGR-1600-020	871	160	343	368	594	283	300	500	162	F25/F30	412	75	165	130
WGR-3200-020	943	250	325	368	700	283	300	500	243	F30/F35	427	90	180	166
WGR-3200-030	989	250	325	414	743	313	312	600	243	F30/F35	453	90	180	174
WGR-6300-020	1053	305	380	368	820	283	300	500	303	F40	472	135	270	509
WGR-6300-030	1099	305	380	414	844	313	312	600	303	F40	498	135	270	517
WGR-6300-040	1163	305	380	478	886	318	372	720	303	F40	596	135	270	527

WGR-Quarter turn Actuator Performances with 3-phase motors⁽⁴⁾

Model WGR ⁽¹⁾	Nom Torque ⁽²⁾ (100%) (Nm)	Min Torque (Nm)	Max Torque ⁽³⁾ (Nm)	Op. Time/90° (secs at 50 Hz)	Op. Time/90° (secs at 60 Hz)	Motor Type
WGR-100/330-**-**	330	132	500	63	52	SM00
WGR-100/330-**-**	330	132	500	42	35	SM01
WGR-100/330-**-**	330	132	500	31	26	SM10
WGR-100/330-**-**	330	132	500	21	17	SM11
WGR-100/330-**-**	330	132	500	16	13	SM04
WGR-100/330-**-**	330	132	500	10	9	SM05
WGR-100-010/1000-**-**	1000	400	1500	63	52	SM10
WGR-100-010/1000-**-**	1000	400	1500	42	35	SM11
WGR-100-010/1000-**-**	1000	400	1500	31	26	SM12
WGR-100-010/1000-**-**	1000	400	1500	21	17	SM13
WGR-100-010/1000-**-**	1000	400	1500	16	13	SM14
WGR-100-010/1000-**-**	1000	400	1500	10	9	SM15
WGR-200-010/2000-**-**	2000	800	3000	125	104	SM10
WGR-200-010/2000-**-**	2000	800	3000	83	69	SM11
WGR-200-010/2000-**-**	2000	800	3000	63	52	SM12
WGR-200-010/2000-**-**	2000	800	3000	42	35	SM13
WGR-200-010/2000-**-**	2000	800	3000	31	26	SM14
WGR-200-010/2000-**-**	2000	800	3000	21	17	SM15
WGR-200-010/2000-**-**	2000	800	3000	10	9	SM16
WGR-400-010/4000-**-**	4000	1600	6000	155	129	SM10
WGR-400-010/4000-**-**	4000	1600	6000	103	86	SM11
WGR-400-010/4000-**-**	4000	1600	6000	78	65	SM12
WGR-400-010/4000-**-**	4000	1600	6000	52	43	SM13
WGR-400-010/4000-**-**	4000	1600	6000	39	32	SM14
WGR-400-010/4000-**-**	4000	1600	6000	26	22	SM15
WGR-400-010/4000-**-**	4000	1600	6000	13	11	SM16
WGR-800-020/8000-**-**	8000	3200	12000	229	196	SM12
WGR-800-020/8000-**-**	8000	3200	12000	153	125	SM13
WGR-800-020/8000-**-**	8000	3200	12000	114	95	SM14
WGR-800-020/8000-**-**	8000	3200	12000	76	64	SM15
WGR-800-020/8000-**-**	8000	3200	12000	57	47	SM21
WGR-800-020/8000-**-**	8000	3200	12000	38	32	SM22
WGR-800-020/8000-**-**	8000	3200	12000	19	16	SM23
WGR-1600-020/16000-**-**	16000	6400	24000	466	389	SM12
WGR-1600-020/16000-**-**	16000	6400	24000	311	259	SM13
WGR-1600-020/16000-**-**	16000	6400	24000	233	194	SM14
WGR-1600-020/16000-**-**	16000	6400	24000	155	130	SM15
WGR-1600-020/16000-**-**	16000	6400	24000	117	97	SM21
WGR-1600-020/16000-**-**	16000	6400	24000	78	65	SM22
WGR-1600-020/16000-**-**	16000	6400	24000	39	32	SM23
WGR-3200-020/32000-**-**	32000	12800	48000	623	519	SM13
WGR-3200-020/32000-**-**	32000	12800	48000	467	389	SM14
WGR-3200-020/32000-**-**	32000	12800	48000	311	259	SM15
WGR-3200-020/32000-**-**	32000	12800	48000	233	195	SM21
WGR-3200-020/32000-**-**	32000	12800	48000	156	130	SM22
WGR-3200-020/32000-**-**	32000	12800	48000	78	65	SM23
WGR-3200-030/32000-**-**	32000	12800	48000	42	35	SM31
WGR-6300-020/63000-**-**	63000	25200	94500	700	583	SM15
WGR-6300-020/63000-**-**	63000	25200	94500	525	438	SM21
WGR-6300-020/63000-**-**	63000	25200	94500	350	292	SM22
WGR-6300-020/63000-**-**	63000	25200	94500	175	146	SM23
WGR-6300-030/63000-**-**	63000	25200	94500	96	80	SM31
WGR-6300-040/63000-**-**	63000	25200	94500	39	33	SM42

See notes for Multiturn Actuator performances



Elga


Scotch-yoke reducer for application on valves requiring high torques at stroke limits (Open/Close). Also used on quarter-turn valves when very high torques are required.

Notes

1. The ** are to be replaced by operating time value at selected frequency (50 or 60 Hz)
2. Nominal output torque settable from 40% (minimum torque) to 100% of indicated value
3. Theoric max output torque. The actual max output torque is a function of speed and motor power supply and may vary from 1.3 to 2 times nominal output torque
4. The performances below are referred to ON/OFF S2-15' or INCHING S4-25%-60 starts/hour duties (IEC34-1)

ELGA Actuator Performances with 3-phase motors⁽⁴⁾

Model ⁽¹⁾	Nom. Torque ⁽²⁾ (100%) (Nm)			Max Torque ⁽³⁾ (Nm)	Op. Time/90° (secs at 50 Hz)	Op. Time/90° (secs at 60 Hz)	ICON2000 Model	Motor Type	Motor Power (KW) at 50Hz	Motor Power (KW) at 60Hz
	Break To Open	Running	End to open							
ELGA-14KR-020/94000-**-	94000	54300	82000	141000	865	721	ICON-020/180-24(29)	SM14	0.286	0.343
ELGA-14KR-020/94000-**-	94000	54300	82000	141000	577	481	ICON-020/180-36(43)	SM15	0.367	0.440
ELGA-14KR-020/94000-**-	94000	54300	82000	141000	433	361	ICON-020/180-48(58)	SM21	0.526	0.631
ELGA-14KR-020/94000-**-	94000	54300	82000	141000	288	240	ICON-020/180-72(86)	SM22	0.789	0.947
ELGA-14KR-020/94000-**-	94000	54300	82000	141000	144	120	ICON-020/180-144(173)	SM23	1.470	1.764
ELGA-14KR-030/94000-**-	94000	54300	82000	141000	69	58	ICON-030/360-144(173)	SM31	3.368	4.042
ELGA-14KR-040/94000-**-	94000	54300	82000	141000	42	35	ICON-040/720-144(173)	SM42	5.818	6.982
ELGA-18KR-020/133000-**-	133000	77000	116000	199500	1330	1108	ICON-020/180-24(29)	SM14	0.286	0.343
ELGA-18KR-020/133000-**-	133000	77000	116000	199500	887	739	ICON-020/180-36(43)	SM15	0.367	0.440
ELGA-18KR-020/133000-**-	133000	77000	116000	199500	665	554	ICON-020/180-48(58)	SM21	0.526	0.631
ELGA-18KR-020/133000-**-	133000	77000	116000	199500	443	369	ICON-020/180-72(86)	SM22	0.789	0.947
ELGA-18KR-020/133000-**-	133000	77000	116000	199500	222	185	ICON-020/180-144(173)	SM23	1.470	1.764
ELGA-18KR-030/133000-**-	133000	77000	116000	199500	133	111	ICON-030/360-144(173)	SM31	3.368	4.042
ELGA-18KR-040/133000-**-	133000	77000	116000	199500	57	48	ICON-040/720-144(173)	SM42	5.818	6.982
ELGA-32KR-030/266000-**-	266000	156000	238000	399000	1272	1060	ICON-030/360-36(43)	SM22	0.789	0.947
ELGA-32KR-030/266000-**-	266000	156000	238000	399000	954	795	ICON-030/360-48(58)	SM30	1.123	1.348
ELGA-32KR-030/266000-**-	266000	156000	238000	399000	636	530	ICON-030/360-72(86)	SM23	1.470	1.764
ELGA-32KR-030/266000-**-	266000	156000	238000	399000	318	265	ICON-030/360-144(173)	SM31	3.368	4.042
ELGA-32KR-040/266000-**-	266000	156000	238000	399000	181	151	ICON-040/720-144(173)	SM42	5.818	6.982
ELGA-32KR-050/266000-**-	266000	156000	238000	399000	75	63	ICON-050/1440-144(173)	SM51	11.636	13.963
ELGA-50KR-030/334000-**-	334000	197000	300000	501000	1280	1067	ICON-030/360-36(43)	SM22	0.789	0.947
ELGA-50KR-030/334000-**-	334000	197000	300000	501000	960	800	ICON-030/360-48(58)	SM30	1.123	1.348
ELGA-50KR-030/334000-**-	334000	197000	300000	501000	640	533	ICON-030/360-72(86)	SM23	1.470	1.764
ELGA-50KR-030/334000-**-	334000	197000	300000	501000	320	267	ICON-030/360-144(173)	SM31	3.368	4.042
ELGA-50KR-040/334000-**-	334000	197000	300000	501000	152	127	ICON-040/720-144(173)	SM42	5.818	6.982
ELGA-50KR-050/334000-**-	334000	197000	300000	501000	65	54	ICON-050/1440-144(173)	SM51	11.636	13.963




Notes



1. Insert bush supplied by BIFFI with unmachined bore. Machining of bore upon request
2. Different values of flange dimensions can be supplied on request
3. Female spigot supplied as a standard. Male spigot supplied on request. Model 1.5K without spigot
4. Fixing bolts or rods supplied by BIFFI only on request, minimum material class required 8.8 UNI37409, ASTM A320-L7

ICON2000 Series Elga

Model	ISO 5211 (2)	Ø d ₁	Ø d ₂ (3)	Ø d ₃	Ø d ₄ (4)	N	h ₁ (3)	h ₂	H	d ₇ Max Stem Acceptance			
										With Insert Bush		One Piece Bush	
										Ø d ₇	Ø d _x	Ø d ₇	Ø d _x
14	F48	580	250	483	M36	12	10	29	340	Ø 160	Ø 185	Ø 200	Ø 228
18	F60	680	290	603	M36	20	12	32	350	Ø 160	Ø 185	Ø 220	Ø 250
32	F60	780	290	603	M36	20	12	32	400	Ø 180	Ø 206	Ø 230	Ø 260
50	SPECIAL	800	315	698	M36	24	10	32	430	Ø 200	Ø 226	Ø 255	Ø 285
80	SPECIAL	890	370	813	M42	24	10	37	585	Ø 250	Ø 282	Ø 300	Ø 338



Lever Position Detail



Standard cable entries:

a = 1" NPT

b = 1 1/2" NPT

ELGA/ICON2000 Series Overall Dimensions

Model	A	a1	a2	a3	B	b1	b2	ØC	D	F	H	h1	h2	Mass Kg
14KR-020	1619	536	778	305	772	283	300	500	200	F48	463	166	320	650
14KR-030	1653	536	778	339	793	313	312	600	200	F48	476	166	320	660
14KR-040	1712	536	778	398	835	318	372	720	200	F48	627	166	320	670
18KR-020	1727	583	839	305	852	283	300	500	230	F60	542	195	383	800
18KR-030	1761	583	839	339	873	313	312	600	230	F60	595	195	383	810
18KR-040	1820	583	839	398	915	318	372	720	230	F60	656	195	383	820
32KR-030	1964	663	1124	339	863	313	312	600	270	F60	632	232	464	960
32KR-040	2064	663	1164	398	1005	318	372	720	270	F60	693	232	464	970
32KR-050	2185	663	1244	478	1049	363	392	860	270	F60	750	232	464	980
50KR-030	2340	710	1291	339	1003	313	312	600	300	SPEC.	633	233	561	1180
50KR-040	2439	710	1331	398	1045	318	372	720	300	SPEC.	694	233	561	1190
50KR-050	2599	710	1411	478	1089	363	392	860	300	SPEC.	751	233	561	2000



Linear Actuator ICON2000L


For specific application on linear valves (gate, globe...) with non-threaded stem, generally to replace piston or diaphragm pneumatic actuators.

Notes

1. The ** are to be replaced by Linear speed value at selected frequency (50 or 60 Hz)
2. Nominal output thrust setttable from 40% (minimum thrust) to 100% of indicated value
3. Theoric max output thrust. The actual max output thrust is a function of speed and motor power supply and may vary from 1.3 to 2 times nominal output thrust
4. The performances below are referred to ON/OFF S2-15' or INCHING S4-25%-60 starts/hour duties (IEC34-1)
5. Referred to Running thrust = 40% Nominal thrust

ICON2000L Linear Actuator Performances with 3-phase motors⁽⁴⁾

Model ⁽¹⁾	Nominal Thrust ⁽²⁾ (100%) (KN)	Min Thrust (KN)	Max Thrust ⁽³⁾ (KN)	Linear Speed ⁽⁵⁾ (mm/secs at 50Hz)	Linear Speed ⁽⁵⁾ (mm/secs at 60Hz)	Motor Type	Mot. Power (KW) at 50 Hz	Mot. Power (KW) at 60 Hz	R
ICON-010L/10-**-	10	4	15	0.6	0.7	SM00	0.030	0.036	40:1
ICON-010L/10-**-	10	4	15	0.9	1.1	SM01	0.046	0.055	40:1
ICON-010L/10-**-	10	4	15	1.2	1.4	SM10	0.071	0.085	20:1
ICON-010L/10-**-	10	4	15	1.4	1.7	SM11	0.106	0.127	20:1
ICON-010L/10-**-	10	4	15	2.2	2.6	SM04	0.142	0.170	20:1
ICON-010L/10-**-	10	4	15	3.6	4.3	SM05	0.213	0.256	20:1
ICON-010L/40-**-	40	16	60	0.6	0.7	SM10	0.071	0.085	40:1
ICON-010L/40-**-	40	16	60	0.9	1.1	SM11	0.106	0.127	40:1
ICON-010L/40-**-	40	16	60	1.2	1.4	SM12	0.122	0.146	20:1
ICON-010L/40-**-	40	16	60	1.4	1.7	SM13	0.184	0.221	20:1
ICON-010L/40-**-	40	16	60	2.2	2.6	SM14	0.286	0.343	20:1
ICON-010L/40-**-	40	16	60	3.6	4.3	SM15	0.367	0.440	20:1
ICON-020L/60-**-	60	24	90	0.8	1.0	SM12	0.122	0.146	40:1
ICON-020L/60-**-	60	24	90	1.2	1.4	SM13	0.184	0.221	40:1
ICON-020L/60-**-	60	24	90	1.6	1.9	SM14	0.286	0.343	40:1
ICON-020L/60-**-	60	24	90	2.4	2.9	SM15	0.367	0.440	40:1
ICON-020L/60-**-	60	24	90	3.2	3.8	SM21	0.526	0.631	20:1
ICON-020L/60-**-	60	24	90	4.8	5.8	SM22	0.789	0.947	20:1
ICON-030L/90-**-	90	36	135	1.0	1.2	SM21	0.526	0.631	80:1
ICON-030L/90-**-	90	36	135	1.5	1.8	SM32	0.500	0.600	40:1
ICON-030L/90-**-	90	36	135	2.0	2.4	SM21	0.526	0.631	40:1
ICON-030L/90-**-	90	36	135	3.0	3.6	SM22	0.789	0.947	40:1
ICON-030L/90-**-	90	36	135	4.0	4.8	SM30	1.123	1.348	20:1
ICON-030L/90-**-	90	36	135	6.0	7.2	SM23	1.470	1.764	40:1
ICON-040L/150-**-	150	60	225	1.6	1.9	SM30	1.123	1.348	80:1
ICON-040L/150-**-	150	60	225	2.4	2.9	SM44	0.840	1.008	40:1
ICON-040L/150-**-	150	60	225	3.2	3.8	SM30	1.123	1.348	40:1
ICON-040L/150-**-	150	60	225	4.8	5.8	SM40	1.684	2.021	40:1
ICON-040L/150-**-	150	60	225	6.4	7.7	SM41	1.939	2.327	20:1
ICON-040L/150-**-	150	60	225	9.6	11.5	SM31	3.368	4.042	40:1



Notes

1. The stem is drawn in fully retracted position.
2. The stem end ($\varnothing d_8$) is left hand thread
3. Only axial loads are permitted
4. F_{nom} is the maximum thrust applicable to the linear thrust block in **dynamic conditions** with torque control set at 100%.
 F_{max} is the maximum thrust applicable to the linear thrust block in **static conditions** with manual override or with motor in stall torque

ICON2000 Series Linear

Model	010L	020L	030L	040L
ISO 5210/DIN3358	F10	F14	F14	F16
F_{nom} (KN)	40	60	80	150
F_{max} (KN)	60	90	135	225
$\varnothing d_1$	125	175	175	210
$\varnothing d_2 f8$	70	100	100	130
$\varnothing d_3$	102	140	140	165
$\varnothing d_4$	M10	M16	M16	M20
$\varnothing d_8$ (left)	M20x1,5	M36x3	M36x3	M42x3
h_1	3	4	4	4
h_2	15	24	24	30
l_7	265	375	480	580
l_2	25	55	55	65
l_4	35	60	60	80
N	4	4	4	4
$S_{(Max\ stroke)}$	100	160	200	300
Mass (Kg)	10	18	22	28

Notes

1. The ** are to be replaced by Linear speed value at selected frequency (50 or 60 Hz)
2. Nominal output thrust settable from 40% (minimum thrust) to 100% of indicated value
3. Theoric max output thrust. The actual max output thrust is a function of speed and motor power supply and may vary from 1.3 to 2 times nominal output thrust
4. The performances below are referred to ON/OFF S2-30' or INCHING S4-25%-600 starts/hour duties (IEC34-1)
5. Referred to Running thrust = 40% Nominal thrust
6. Ambient temperature from -55°C to 65°C

ICON2000L Linear Actuator Performances with 3-phase motors⁽⁴⁾

Model ⁽¹⁾	Nominal Thrust ⁽²⁾ (100%) (KN)	Min Thrust (KN)	Max Thrust ⁽³⁾ (KN)	Linear Speed ⁽⁵⁾ (mm/secs at 50Hz)	Linear Speed ⁽⁵⁾ (mm/secs at 60Hz)	Motor Type	Mot. Power (KW) at 50 Hz	Mot. Power (KW) at 60 Hz	R
ICON-010L/10-**-	10	4	15	0.6	0.7	TM00	0.030	0.036	40:1
ICON-010L/10-**-	10	4	15	0.9	1.1	TM01	0.046	0.055	40:1
ICON-010L/10-**-	10	4	15	1.2	1.4	TM10	0.071	0.085	20:1
ICON-010L/10-**-	10	4	15	1.4	1.7	TM11	0.106	0.127	20:1
ICON-010L/10-**-	10	4	15	2.2	2.6	TM04	0.142	0.170	20:1
ICON-010L/10-**-	10	4	15	3.6	4.3	TM05	0.213	0.256	20:1
ICON-010L/40-**-	40	16	60	0.6	0.7	TM10	0.071	0.085	40:1
ICON-010L/40-**-	40	16	60	0.9	1.1	TM11	0.106	0.127	40:1
ICON-010L/40-**-	40	16	60	1.2	1.4	TM12	0.122	0.146	20:1
ICON-010L/40-**-	40	16	60	1.4	1.7	TM13	0.184	0.221	20:1
ICON-010L/40-**-	40	16	60	2.2	2.6	TM14	0.286	0.343	20:1
ICON-010L/40-**-	40	16	60	3.6	4.3	TM15	0.367	0.440	20:1
ICON-020L/60-**-	60	24	90	0.8	1.0	TM12	0.122	0.146	40:1
ICON-020L/60-**-	60	24	90	1.2	1.4	TM13	0.184	0.221	40:1
ICON-020L/60-**-	60	24	90	1.6	1.9	TM14	0.286	0.343	40:1
ICON-020L/60-**-	60	24	90	2.4	2.9	TM15	0.367	0.440	40:1
ICON-020L/60-**-	60	24	90	3.2	3.8	TM21	0.526	0.631	20:1
ICON-020L/60-**-	60	24	90	4.8	5.8	TM22	0.789	0.947	20:1
ICON-030L/90-**-	90	36	135	2.0	2.4	TM21	0.526	0.631	40:1
ICON-030L/90-**-	90	36	135	3.0	3.6	TM22	0.789	0.947	40:1
ICON-030L/90-**-	90	36	135	4.0	4.8	TM30	1.123	1.348	20:1
ICON-030L/90-**-	90	36	135	6.0	7.2	TM23	1.470	1.764	40:1
ICON-040L/150-**-	150	60	225	3.2	3.8	TM30	1.123	1.348	40:1
ICON-040L/150-**-	150	60	225	4.8	5.8	TM40	1.684	2.021	40:1
ICON-040L/150-**-	150	60	225	9.6	11.5	TM31	3.368	4.042	40:1

For any further information you may require please contact Biffi Sales office;
tel. ++39-0523.944411, fax ++39-0523.943923,
e-mail: sales@biffi.it



ICOM2000-BU-E Rev. 6 Feb 2008



Biffi Italia s.r.l.

Headquarters, Sales department, 29017 Fiorenzuola d'Arda - Italy tel. +39 0523 944411 fax +39 0523 943923 e-mail biffi_italia@biffi.it

A **tyco** INTERNATIONAL LTD. COMPANY

website: www.biffi.it